

THREE PHASE & DUAL MPPT

SE 10/12/15KTL-D3/G2P, SE 17/20/22/25KTL-D3/G2



SUPERIOR EFFICIENCY

- Maximum efficiency 98.4%
- Max String Current 20A, compatible with 600W+ modules
- 150% PV configuration, 110% output overload



HIGH RELIABILITY

- Die-cast aluminum case, IP66 waterproof and dustproof, C5 anti-corrosion
- DC /AC SPD, AFCI detection optional
- Compatible with wide power grid voltage and high harmonic power grid environment



INTELLIGENT MAINTENANCE

- App quick commissioning
- Remote configuration and upgrade
- Supports export control

Model	SE 10KTL-D3/G2P	SE 12KTL-D3/G2P	SE 15KTL-D3/G2P	SE 17KTL-D3/G2	SE 20KTL-D3/G2	SE 22KTL-D3/G2	SE 25KTL-D3/G2
Efficiency							
Max. Efficiency	98.3%	98.3%	98.4%	98.4%	98.4%	98.4%	98.4%
European Efficiency	97.8%	97.8%	98.0%	98.0%	98.0%	98.0%	98.0%
Input (PV)							
Max. Input Voltage				1100V			
Max. PV configuration				150%			
Rated Input Voltage				620V			
Max. Input Current	30A+15A				2*30A		
Max. Short Circuit Current	40A+20A				2*40A		
Start Input Voltage				180V			
MPPT Operating Voltage Range				160V-1000V			
Max. Number of PV Strings	3 (2/1)				4 (2/2)		
No. of MPPTs					2		
Output (Grid)							
Rated AC Active Power	10,000W	12,000W	15,000W	17,000W	20,000W	22,000W	25,000W
Max. AC Apparent Power	11,000VA	13,200VA	16,500VA	18,700VA	22,000VA	24,200VA	25,000VA
Max. AC Active Power (PF=1)	11,000W	13,200W	16,500W	18,700W	22,000W	24,200W	25,000W
Max. AC Output Current	3*16.8A	3*20.2A	3*25.3A	3*28.6A	3*33.7A	3*37A	3*39.8A
Rated AC Voltage				380V / 400V / 415V, 3W+N+PE			
AC Voltage Range①				260V-510V (adjustable)			
Rated Grid Frequency				50Hz / 60Hz			
Grid Frequency Range②				45Hz-55Hz / 55Hz-65Hz (Adjustable)			
THDI				<3%@Rated Power			
DC Current Injection				<0.5%@Rated Current			
Power Factor				> 0.99 Rated power (Adjustable 0.8 Leading - 0.8Lagging)			
Protection							
DC switch					Support		
Anti-islanding protection					Support		
AC overcurrent protection					Support		
AC short circuit protection					Support		
DC reverse connection					Support		
Surge Arrester					AC Type III (Type II optional) / DC Type III (Type II optional)		
Insulation detection					Support		
String current detection					Optional		
Leakage current protection					Support		
General							
Topology					Transformerless		
IP Rating					IP66		
Night Self Consumption					<1W		
Cooling				Natural cooling			Fan cooling
Operating Temperature Range						-25°C-60°C	
Relative Humidity Range						0-100%	
Max. Operating Altitude						4000m	
Noise						<45dB	
Dimensions (W*H*D)						398mm*460mm*190mm	
Weight						23Kg	
HMI & COM							
Display						Wireless & APP +LED, LCD (Optional)	
Communication						RS485, WiFi / GPRS / 4G (Optional)	
Certification							
Safety						IEC62109-1, IEC62109-2	
Grid Code						VDE-AR-N 4105, EN 50549-1, CEI 0-21, UNE 206006/206007-1, UNE 217001, IEC 61727/62116	
Warranty						5 Years	

Remarks: • ①②The range of output voltage and frequency may vary depending upon different grid codes.
• Specifications are subject to change without advance notice.