

## SINGLE PHASE & DUAL MPPT

SE 4/5/6KTL-D1/G2P

Application: Family Use



### SUPERIOR EFFICIENCY

- Maximum efficiency of 98.2%
- String current of 15A, compatible with high power modules
- 150% PV configuration and 110% output overload

### HIGH RELIABILITY

- IP65 waterproof and dustproof
- Compatible with a wide range of power grid voltage and high harmonic power grid environments
- Optional DC/AC SPD, AFCI detection and C5 anti-corrosion features for added protection

### INTELLIGENT MAINTENANCE

- Remote configuration and upgrade
- Power export control supported

Model	SE 4KTL-D1/G2P	SE 5KTL-D1/G2P	SE 6KTL-D1/G2P
<b>Efficiency</b>			
Max. Efficiency	98.0%	98.2%	98.2%
European Efficiency	97.0%	97.3%	97.4%
<b>Input(PV)</b>			
Max. Input Voltage		550V	
Max. PV Configuration (STC)		150%	
Rated Input Voltage		360V	
Max. Input Current		30A (2*15A)	
Max. Short Circuit Current		40A (2*20A)	
Start Input Voltage		90V	
MPPT Operating Voltage Range		70V-540V	
Max. Number of PV Strings		2 (1/1)	
No. of MPPTs		2	
<b>Output(Grid)</b>			
Rated AC Active Power	4,000W	5,000W	6,000W
Max. AC Apparent Power	4,400VA	5,500VA	6,000VA
Max. AC Active Power (PF=1)	4,400W	5,500W	6,000W
Max. AC Output Current	20A	25A	27.3A
Rated AC Voltage	220V/230V, L+N+PE		
AC Voltage Range①	160V-300V (Adjustable)		
Rated Grid Frequency	50Hz / 60Hz		
Grid Frequency Range②	45Hz-55Hz / 55Hz-65Hz (Adjustable)		
THDI	<3% (Rated Power)		
DC Current Injection	<0.5%In		
Power Factor	>0.99 Rated power (Adjustable 0.8 LD-0.8 LG)		
<b>Protection</b>			
DC Switch		Support	
Anti-islanding Protection		Support	
AC Overcurrent Protection		Support	
AC Short Circuit Protection		Support	
DC Reverse Connection		Support	
Surge Arrester		DC Type III (Optional) / AC Type III	
Insulation Detection		Support	
Leakage Current Protection		Support	
<b>General</b>			
Topology		Transformerless	
IP Rating		IP65	
Night Self Consumption		<1W	
Cooling		Natural cooling	
Operating Temperature Range		-25°C-60°C	
Relative Humidity Range		0-100%	
Max. Operating Altitude		4000m	
Noise (typical)		30dB	
Dimensions (W*H*D)		350mm*347mm*137mm	
Weight		8.5kg	
<b>HMI &amp; COM</b>			
Display		Wireless & APP+LED, LCD (Optional)	
Communication		Optional: WiFi / GPRS / RS485 / LAN	
<b>Certification</b>			
Safety		IEC62109-1, IEC62109-2	
Grid Code		DE-AR-N 4105, EN 50549-1, CEI 0-21, UNE 206001/206002-1, IEC 61727/62116, ORDINANCE n°140 2022, IEEE 1547, UL 1741, AS 4777, VDE 0126-1	
<b>Warranty</b>			
			5 Years

Remarks: • ①②The range of output voltage and frequency may vary depending on different grid codes.  
• Specifications are subject to change without advanced notice.