

**THREE PHASE & DUAL MPPT**

SE 5/6/8/10/12/15KTL-D3/G2

Application: Residential &amp; Small C&amp;I use

**SUPERIOR PERFORMANCE**

- Maximum efficiency of 98.3%
- Large string current, compatible with large PV modules
- Wide voltage range, compatible with various power grids
- Compact for easy installation

**HIGH RELIABILITY**

- IP66 protection level for outdoor installation
- Optional: DC/AC Type II SPD
- Optional: AFCI function

**INTELLIGENT MAINTENANCE**

- Power consumption monitoring
- Remote configuration and upgrade
- Quick commissioning via mobile app
- Multiple I/O and communication configurations



www.senergytec.com

Shenzhen Senergy Technology Co., Ltd.

Tel: +86-755-8524-5541 ext. 2800

Email: salesglobal@senergytec.com

Address: 11th floor, Building 6, Skyworth Innovation Valley, No. 8 Tangtou No. 1 Road, Bao'an District, Shenzhen, P.R.China

Model	SE 5KTL-D3/G2	SE 6KTL-D3/G2	SE 8KTL-D3/G2	SE 10KTL-D3/G2	SE 12KTL-D3/G2	SE 15KTL-D3/G2
<b>Efficiency</b>						
Max. Efficiency	98.2%			98.3%		
European Efficiency	97.8%					
<b>Input (PV)</b>						
Max. Input Voltage	1100V					
Max. PV Configuration	150%					
Rated Input Voltage	620V					
Max. Input Current	2*15A			15A+2*15A		
Max.Short Circuit Current	2*20A			20A+2*20A		
Start Input Voltage	180V					
MPPT Operating Voltage Range	160V-1000V					
Max. Number of PV Strings	2 (1/1)			3 (1/2)		
No. of MPPTs	2					
<b>Output (Grid)</b>						
Rated AC Active Power	5,000W	6,000W	8,000W	10,000W	12,000W	15,000W
Max. AC Apparent Power	5,500VA	6,600VA	8,800VA	11,200VA	13,200VA	16,700VA
Max. AC Output Current	3*8.4A	3*10.1A	3*13.4A	3*17A	3*20.2A	3*25.3A
Rated AC Voltage	380V / 400V / 415V, 3W+N+PE					
AC Voltage Range <sup>①</sup>	260V-510V (Adjustable)					
Rated Grid Frequency	50Hz / 60Hz					
Grid Frequency Range <sup>②</sup>	45Hz-55Hz / 55Hz-65Hz (Adjustable)					
THDI	<3%@Rated Power					
DC Current Injection	<0.5%@Rated Current					
Power Factor	> 0.99 Rated power (Adjustable 0.8 LD - 0.8 LG)					
<b>Protection</b>						
DC Switch	Yes					
Anti-Islanding Protection	Yes					
AC Overcurrent Protection	Yes					
AC Short Circuit Protection	Yes					
DC Reverse Protection	Yes					
Surge Arrester	DC Type III(Type II optional) / AC Type III(Type II optional)					
Insulation Detection	Yes					
Leakage Current Protection	Yes					
<b>General</b>						
Topology	Transformerless					
IP Rating	IP66					
Night Self Consumption	< 1W (Standard)					
Cooling	Natural cooling					
Operating Temperature Range	-25°C-60°C					
Relative Humidity Range	0-100%					
Max. Operating Altitude	4000m					
Dimensions (W*H*D)	398mm*460mm*190mm					
Weight	16.8Kg			18.7Kg		
<b>HMI &amp; COM</b>						
Display	Wireless & APP +LED, LCD (Optional)					
Communication	RS485, Optional: WiFi / GPRS / LAN					
<b>Certification</b>						
Safety	IEC62109-1, IEC62109-2					
Grid Code	VDE-AR-N 4105, EN 50549-1, CEI 0-21, UNE 206006/206007-1, RD 1699/661&413, IEC 61727/62116, AS4777.2					
Warranty	5 Years					

**Remarks :** • ①②The range of output voltage and frequency may vary depending on different grid codes.  
• Specifications are subject to change without advanced notice.